

140TS2

DIRECT MOUNT EJECTOR SCRAPER



14yd³ HEAPED CAPACITY



97.5" CUTTING WIDTH



200-500 RECOMMENDED HORSEPOWER



We've taken our most popular size scraper and made it more industrial. This robust design is the perfect fit for serious field drainage work to improve your crop yield. The 140TS2 is sized correctly to meet the sweet spot of maneuverability, hauling capacity, and horsepower. With a 25% tractor to 75% scraper weight transfer ratio, Ashland's direct mount scrapers require less horsepower than traditional dolly wheel scrapers; which means the 140TS2 will be easier to load and require less effort for operators.

GET IMPROVED FLOTATION WITH THE LGP EDITION

Designed for customers who need greater flotation in soft conditions. The 23.5 x 25 OTR rear tires have a longer rolling radius to keep you moving when the going gets tough.



140TS2



140TS2-LGP

EQUIPMENT FEATURES

- › Arched bowl sides keep material collected within the bowl rather than spilling over the sides onto the bowl side frame, pivot joints on the front section and apron cylinders, which translates into longer life and less downtime.
- › The apron arm has been changed to provide large clearance between the arm and the side frame when fully closed.
- › All the outboard pivoting supports have been changed from a 90 degree to a stronger 45 degree outboard support. This provides a large support area and more welded surface.
- › The rack is tilt-able and can be positioned backwards 30 degrees for top loading, forward 30 degrees for normal scraper operations or flat for reduced transport height.
- › Convenient grease zerks in all wheel hubs
- › The rear channel for the plastic slides have deeper engagement to provide longer life of the plastic slide.
- › Protruding boron through hardened center stinger blade (optional serrated), left and right corner blades and side router bits
- › 20.5 x 25 OTR Tires 140TS2
23.5 x 25 OTR Tires on LGP Edition
- › Pushbar Extension
- › Heavy duty scraper swivel yoke (requires specialized tractor hitch)
- › Dual-plated floor
- › Trunnion-block with improved grease retention
- › Heavy wall front section with taper trailing arms
- › Laser pad on cross-member
- › 1 year structural Warranty /
2 year hydraulic cylinder warranty

SPECIFICATIONS

Heaped Capacity	14 yd ³ (10.7 m ³)
Recommended HP	250-500 hp (186-373 kw)
Width of Cut	97.5" (247.6 cm)
Apron Clearance	57" (144.8 cm)
Ejector Cylinder (1)	4.5" x 54" (114 mm x 1,372 mm)
Apron Cylinder (2)	4" x 13" (102 mm x 330 mm)
Lift Cylinder (2)	5" x 20" (127 mm x 508 mm)
Laser / GPS Bracket	Standard
Standard Tires	(2) 18.4 x 26
LGP Edition Tires	(2) 20.5 x 25
Overall Width	110" (279.4 cm)
Overall Length	333" (845.8 cm)
Overall Height	85" (215.9 cm)
Weight (w/ std. bias tire)	14,400 lb (6,532 kg)
LGP Edition Weight (w/ std. bias tire)	15,173 lb (6,882 kg)



**DOUBLE CAPACITY
TO 28 CU. YDS. WITH
A TANDEM SETUP**