



DIRECT MOUNT SERIES

# 1228



## VERSATILITY AT ITS FINEST

The K-Tec™ 1228 has versatility, making it one of K-Tec's most popular models. The 1228 "Sand Shark" is designed to load well in all conditions and specializes in low ground pressure projects, and is proficient in sandy soil.

# 1228 SPECIFICATIONS


General Specifications	Standard	Metric
Heaped Capacity (ISO)	28 Cubic Yards	21.4 Cubic Metres
Struck Capacity	18.5 Cubic Yards	14.1 Cubic Metres
Max Loading Rating	68,000 lbs	30,844 kgs
Bucket Dimensions	12' W x 4' H x 11' L	3.66m W x 1.22m H x 3.35m L
Cutting Width	12'	3.66m
Cutting Edge	3-Piece Blade	3-Piece Blade
Gate Opening	78"	1.98m
Rack Height (Tiltable)	3'	0.91m
Gate Cylinders	4.5" x 26.5"	114mm x 673mm
Lift Cylinders	5.5" x 32"	140mm x 813mm
Ejector Cylinder	5.5" x 76"	140mm x 1,930mm
Transport Cutting Edge Clearance	28"	0.71m
Hitch Pin to Rear Axle Length	30'	9.14m
Turning Radius	26'	7.92m
Wrap Around Mud Scrapers	Standard	Standard
Radial Tires (4)	23.5 R25	23.5 R25

### K-Tec Scraper Features




Optional Upgrades	
Floater Tires (2) + Rims & Axle Assembly	1000/50 R25 1050/50 R32
Brake System	4 caliper disc brakes


### Recommended Power Units



Agricultural Tractors  
300HP +/220 KW +



Construction Tractors  
400HP +/298 KW +



Dozers  
230HP - 350HP /171 KW - 260 KW

Transportation Measures	Standard	Metric
Overall Width	14'	4.27m
Overall Height	8' 10"	2.68m
Overall Length	36' 7"	11.15m
Shipping Weight	29,550 lbs	13,403 kgs

Specifications are subject to change without notice.

### Gallery

Sand + Clay / Mississippi, USA



Clay / Kansas, USA



Coal / Indiana, USA



Sand + Topsoil / Ohio, USA



Topsoil + Clay / Virginia, USA



Topsoil / Manitoba, Canada



Topsoil + Clay / Saskatchewan, Canada

